



NOTE:

1. TN TYPE
2. DRIVING METHOD: STATIC
3. OPERATING VOLTAGE: 3.0 VOP
4. OPERATING TEMP: 0° ~ 50°C
5. STORAGE TEMP: -10° ~ 60°C
6. VIEWING DIRECTION: 6:00
7. POLARIZER MODE: REFLECTIVE POSITIVE
8. CONNECTION: PIN TYPE

PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
COM1	COM1	5G	5E	5D	5C	4E	4D	4C	3E	3D	3C	P2	2E	2D	2C	P1	1E	1D	1C	1B
PIN	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
COM1	1A	1F	1G	2B	2A	2F	2G	3B	3A	3F	3G	COL1	4B	4A	4F	4G	COL2	5B	5A	5F

DWN	Bauing	UNIT	mm	CUST. MODEL	
CKD		SCALE		MODEL	ASI-M201216
APPD				DATE	NOV-21-2018

1	INITIAL REVISION		NOV-21-2018
REV.	MODIFY CONTENT		DATE

ALL SHORE INDUSTRIES, INC

NAME	
PAGE	1/1